



TIG™780-10 is environmentally safe silicone-based thermal grease designed to solve overheating and reliability issues ◦

TIG™780-10 is presenting thermal paste products. They serve to moisten the contact surface sufficiently so as to form an interface of extremely low thermal impedance. Consequently, the heat dissipation efficiency is far superior to that offered by others.

Features And Benefits

- » Low thermal resistance of 0.15 °C-in²/W
- » Non-toxic and environmentally safe
- » Outstanding electrical insulation properties
- » Thoroughly wets out contact surfaces to create low thermal resistance

Application

- » Microprocessors
- » Chipsets
- » Graphic processing chips
- » IGBT
- » TO220, TO240, and other standard packages

Typical Properties of TIG780-10 Series

Color	White	Visual	Evaporation (TML)	0.23% / 200°C @ 24 hrs	ASTM E595
Compostion	Metal oxide filled silicone oil	*****	Viscosity	1000K cps @ 25°C	Brookfield RVF,#7
Thermal Conductivity	1.0 W/mK	ASTM D5470	Continuous Use Temp	- 45 To 200 °C	*****
Specific Gravity	2.13g/cm ³	ASTM 2240	Thermal Impedance @50 psi	0.15°C -in ² /W	ASTM D5470

Package

TIG™780-10 Series is available in 1kg (pint container), 3kg (quart container), and 10kg (gallon container) or custom packaged in syringes for automated applications.

Storage:

Store from 20° C to 35° C with a maximum humidity of 50%. Do not store in freezer or refrigerator below 10° C.

If you want to know our thermal Products, you can visit our website . <http://www.ziitek.com>



Gap Fillers | Pouring sealant | Silicon tape | Thermally Conductive paste | Flake graphite | Thermally Conductive Insulators | Ceramic heat sinks
| Thermally Conductive plastic | Thermally Conductive Adhesive Tapes

Canada:
Tel: +001-604-2998559
E-mail: sales@thermazig.com

Taiwan:
Tel: +886-2-22771007
Fax: +886-2-22771075
E-mail: jerry@ziitek.com.tw

Dongguan:
Tel: +86-769-38801208
Fax: +86-769-83791290
E-mail: angus@ziitek.com

Kunshan:
Tel: +86-512-57816297
Fax: +86-512-57816327
E-mail: kelvin@ziitek.com

Chengdu:
Tel: +86-28-62379168
Fax: +86-28-62379168
E-mail: david_cd@ziitek.com